







CATENA OE CON PERNI ESTESI DOPPI 1 LATO ISO-UNI

P. SPORGENTI DOPPI 1 LATO ISO CHAIN OE WITH DUPLEX SIDE EXTENDED PINS ISO-UNI



ISO STANDARD

REF.	A - PITCH (MM)	B - INSIDE WIDTH	C - ROLLER DIAM MIN	E - PLATE WIDTH INNER MAX	F - PLATE WIDTH OUTER MAX	G - PIN DIAM. MAX	H1 - PIN LENGTH MAX	V1	ISO606 TENSILE STRENGTH (NEWTONS) MIN
04B1	6.000	2.800	4.000	0.600	0.600	1.850	12.500	5.3	3000
05B1	8.000	3.000	5.000	0.760	0.760	2.310	13.600	6.4	4400
06B1	9.525	5.720	6.350	1.290	1.040	3.280	23.000	11.3	8900
08B1	12.700	7.750	8.510	1.550	1.550	4.450	30.400	14.8	17800
10B1	15.875	9.650	10.160	1.550	1.550	5.080	35.400	17.6	22200
12B1	19.050	11.680	12.070	1.810	1.810	5.720	41.400	20.7	28900
16B1	25.400	17.020	15.880	4.120	3.100	8.280	66.800	33.3	60000
20B1	31.750	19.560	19.050	4.620	3.610	10.190	77.900	38.3	95000
24B1	38.100	25.400	25.400	6.100	5.080	14.630	101.000	50.4	160000