

Lubri System Oil SA-02



Condition Monitoring and Lubrication

BOLOGNA - ITALY



Lubri System Oil SA-02

LUBRI SYSTEM OIL SA-02

It allows to manage 2 independent lubrication channels and up to 2 outputs for each channel.
 Each channel has its own timer for setting the dispensing intervals and an enabling switch.
 Ideal for the lubrication of mechanical components in movement of any kind.
 Usable with different types of lubrication.

TECHNICAL DATA

Power:	24 VDC
Consumption:	4 A (max)
Operating Temperature:	From 0°C to 50°C
Length Max. pipes	5 mt
Diameter pipes	4x2 mm
Time ON (provision)	0,5 sec. - 10 sec.
Time OFF (stop)	30 sec. - 45 min.
Capacity tank	2000 CC
Viscosity lube:	2 < ISO VG < 460
Dry Weight:	2800 g.
Dimensions	250 x 250 x 140 mm
Interlocking fixing holes X	185 mm <X< 225mm



- 1 Dual timer for setting the lubrication cycle
- 2 Switches for enabling one or both of the lubrication channels
- 3 Window for visual inspection of the lubricant level
- 4 Double output for each lubrication

ACCESSOIRES



. Adjustable dispensing unit



A



B

. Examples of nozzles for applying the lubricant

EXIT CONFIGURATIONS



. 1 exit per channel



. 2 exits per channel

. For any additional information, please contact us directly